AMENDMENT TO THE CLAIMS

1. (previously amended) A colored data storage media, comprising:

a substrate comprising colorant and plastic, wherein the substrate has a transmissivity of about 70% to about 85% at a readback laser wavelength when traversing a 1.2 mm thick colored substrate.

- 2. (original) The storage media of Claim 1, wherein the substrate comprises up to about 5 wt% of the colorant, based upon the entire weight of the substrate.
- 3. (o iginal) The storage media of Claim 2, wherein the substrate comprises up to about 1 wt% of the colorant.
- 4. (original) The storage media of Claim 3, wherein the substrate comprises less than about 0.5 wt% of the colorant.
- 5. (previously amended) The storage media of Claim 1, wherein the transmissivity is about 75% to about 80%.
- 6. (previously amended) The storage media of Claim 1, wherein the transmissivity is about 75% to about 85%.
- 7. (previously amended) The storage media of Claim 1, wherein the plastic is selected from the group consisting of thermoplastics and thermosets.

- 8. (previously amended) The storage media of Claim 7, wherein the thermoplastic is selected from the group consisting of polyvinyl chloride, polyolefins, polyesters, polyamides, polysulfones, polyimides, polyether im des, polyether sulfones, polyphenylene sulfides, polyether ketones, polyether ether ketones, ABS resins, polystyrenes, polybutadiene, polyacry ates, polyacrylonitrile, polyacetals, polycarbonates, polyphenylene ethers, ethylene-vinyl acetate copolymers, polyvinyl acetate, liquid crystal polymers, ethylene-tetrafluoroethylene copolymer, aromatic polyesters, polyvinyl fluoride, polyvinylidene fluoride, polyvinylidene chloride, Teflons, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermoplastics.
- 9. (previously amended) The storage media of Claim 7, wherein the thermoplastic is selected from the group consisting of polyethylene, chlorinated polyethylene, polypropylene, polyethylene terephthalate, polybutylene terephthalate, polycyclohexylmethylene terephthalate, hydrogenated polystyrenes, syndiotactic and atactic polystyrenes, polycyclohexyl ethylene, styrene-co-actylonitrile, styrene-co-maleic anhydride, polymethylmethactylate, methyl methactylate-polyimide copolymers, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermoplastics.
- 10. (previously amended) The storage media of Claim 7, wherein the thermoset is selected from the group consisting of epoxy, phenolic, alkyds, polyester, polyimide, polyurethane, mineral filled silicone, bis-maleimides, byanate esters, vinyl, and benzocyclobutene resins, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermosets.

8CL7332

(GP1-0031)

11. (previously amended) A colored data storage media, comprising:

a substrate comprising coloran: and plastic, wherein the substrate has a transmissivity of about 85% or less at a readback laser wavelength when traversing a 1.2 mm thick colored substrate; and

wherein the substrate further comprises visual effects selected from the group consisting of glass, met al, titanium dioxide, mica, angular metamerism materials, and combinations comprising at least one of the foregoing visual effects.

- 12. (previously amended) The storage media of Claim 11, where in the visual effects have a geometry selected from the group consisting of chips, particles, and combinations comprising at least one of the foregoin; geometries.
- 13. (previously amended) The storage media of Claim 11, where in the visual effects are in the form of flakes.
- 14. (previously amended) The storage media of Claim 11, wherein the transmissivity is about 70% to about 85%.
 - 15. (previously amended) A colored data storage media, comprising:

a substrate comprising colorant and plastic, wherein the substrate has a transmissivity of about 85% or less at a readback laser v'avelength when traversing a 1.2 mm thick colored substrate; and

wherein the colorant further comprises a fluorescent material having a fluorescent color emission wavelength which is not equal to the readback laser wavelength.

16. (previously amended) The storage media of Claim 15, wherein the fluorescent color emission wavelength is different than the readback laser wavelength by at least about ±10nm.

CANTOR COLBURN, LL

8CL7332 (GP1-0031)

- 17. (previously amended) The storage media of Claim 15, wherein the fluorescent color emission was elength is different than the readback laser wavelength by at least about ±20nm.
- 18. (previously amended) The storage media of Claim 15, wherein the transmissivity is about 70% to about 85%.
 - 19. (previously amended) A colored data storage media, comprising:

a substrate comprising colorant and plastic, wherein the substrate has a transmissivity of about 85% or less at a readback laser wavelength when traversing a 1.2 mm thick colored substrate; and

wherein the plastic is polycarbonate, and the polycarbonate comprises structural units of the formula (I):

$$R^{1}-O$$
 (I)

in which at least about 60 percent of the total number of R¹ groups are aromatic organic radicals and the balance are aliphatic, ¿licyclic, or aromatic radicals.

20. (previously amended) The storage media of Claim 19, wherein the transmissivity is about 70% to about 85%.

21. (previously amended) A colored data storage media, comprising:

a substrate comprising colorant and plastic, wherein the substrate has a transmissivity of about 85% or less at a readback laser wavelength when traversing a 1.2 mm thick colored substrate; and

wherein the plastic is polycarbonate, and the polycarbonate is produced by the interfacial reaction of dihydroxy compounds having general formula (III) as follows:

OH
$$X_p$$
 OH $(\mathbb{R}_p)^d$ OH

wherein R^a and R^b each, independently, represent a halogen atom or a monovalent hydrocarbon group; p and q are each independently integers from 0 to 4; and X^a represents one of the groups of formula (IV):

wherein R^c and R^d each independently represent a hydrogen atom or a monovalent linear or cyclic hydrogarbon group and R^c is a divalent hydrogarbon group.

- 22. (previously amended) The storage media of Claim 21, wherein the transmissivity is about 70% to about 85%.
 - 23. (previously amended) A colored data storage media, comprising:

a substrate comprising a fluorescent colorant and plastic, wherein the substrate has a fluorescent color emission wavelength which is not equal to the readback laser wavelength and has a transmissivity of about 70% to about 90% at the laser readback wavelength.

24. (previously amended) The storage media of Claim 23, wherein the fluorescent color emission wavelength is different than the readback laser wavelength by at least about ±10mm.



- 25. (previously amended) The storage media of Claim 24, wherein the fluorescent color emission wavelength is different than the readback laser wavelength by at least about ±15 nm.
- 26. (previously amended) The storage media of Claim 25, wherein the fluorescent color emission wavelength is different than the readback laser wavelength by at least about ±20nm.
- 27. (previously amended) The storage media of Claim 23, wherein the plastic is selected from the group consisting of thermoplastics and thermosets.
- 28. (previously amended) The storage media of Claim 27, wherein the thermoplastic is selected from the group consisting of polyvinyl chloride, polyolefins, polyesters, polyamides, polysulfones, polyimides, polyether imides, polyether sulfones, polyphenylene sulfides, polyether ketones, polyether ether ketones, ABS resins, polystyrenes, polybutadiene, polyacrylates, polyacrylonitrile, polyacetals, polycarbonates, polyphenylene ethers, ethylene-vinyl acetate copolymers, polyvinyl acetate, liquid crystal polymers, ethylene-tetrafluoroethylene copolymer, aromatic polyesters, polyvinyl fluoride polyvinylidene fluoride, polyvinylidene chloride, Teflons, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermoplastics.
- 29. (previously amended) The storage media of Claim 28, wherein the thermoplastic is selected from the group consisting of polyethylene, chlorinated polyethylene, polypropylene, polyethylene terephthalate, polybutylene terephthalate, polycyclohexylmethylene terephthalate, hydrogenated polystyrenes, syndiotactic and atactic polystyrenes, polycyclohexyl ethylene, styrene-co-acrylonitrile, styrene-co-maleic anhydride, polymethylmethacrylate, methyl methacrylate-polyimide copolymers, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermoplastics.

30. (previously amended) The storage media of Claim 28, wherein the polycarbonate comprises structural units of the formula (I):

$$-R^1-O$$
 (I)

in which at least about 60 percent of the total number of R¹ groups are aromatic organic radicals and the balance are aliphatic, alicyclic, or aromatic radicals.

31. (previously amended) The storage media of Claim 30, wherein the polycarbonate is produced by the interfacial reaction of dihydroxy compounds having general formula (III) as follows:

$$OH \xrightarrow{(R^b)_p} X^a \xrightarrow{(R^b)_q} OH$$

wherein R^a and R^b each, independently, represent a halogen atom or a monovalent hydrocarbon group; p and q are each independently integers from 0 to 4; and X^a represents one of the groups of formula (IV):

wherein R^c and R^d each independently represent a hydrogen atom or a monovalent linear or cyclic hydrocarbon group and R^c is a divalent hydrocarbon group.

32. (previously amended) The storage media of Claim 27, wherein the thermoset is selected from the group consisting of epoxy, phenolic, alkyds, polyester, polyimide, polyurethane, mineral filled silicone, bis-maleimides, cyanate esters, vinyl, and benzocyclobutene resins, and blends, copolymers, mixtures, reaction products and composites comprising at least one of the foregoing thermosets.

- 33. (previously amended) The storage media of Claim 23, further comprising a layer disposed adjacent to the substrate, wherein the layer is selected from the group consisting of protective layer(s), dielectric layer(s), data storage layer(s), and reflective layer(s), and combinations comprising at least one of the foregoing layers.
 - 34. (canceled)
- 35. (previously amended) The storage media of Claim 23, wherein the substrate has a transmissivity of about 70% to about 85%.